



## WOYR8.E177511

## Switches, Appliance and Special Use Certified for Canada - Component

If you notice a change to your Woyr8 Listing Card, click [here](#) to learn more.

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

## Switches, Appliance and Special Use Certified for Canada - Component

[See General Information for Switches, Appliance and Special Use Certified for Canada - Component](#)

WON WOO PRECISION CO LTD

E177511

175-3 KALGOT-DONG

OSAN-SHI, KYONGGI-DO 447-310 REPUBLIC OF KOREA

Investigated to CAN/CSA-C22.2 No. 61058-1

						Pol/	Endurance					
Cat. No.	Load	Amps	Volts	Hz	Temp (°C)	Thr/ Cir	30C cycle	55C cycle	IP	Dis (mm)	SPCA	Std. Ed.
Push Button												
S5 f/b suffix	R	5	125	50-60	130	1/1 or 1/2-1.2 or 2.	6K	50K	40	micro	11N02, 14N03	2005-09-30
	R	5	250	50-60	130	1/1 or 1/2-1.2 or 2.	6K	50K	40			
	R	0.1	48	DC	130	1/1 or 1/2-1.2 or 2.	6K	50K	40			
SZM-V01 f/b numbers or blank, f/b F, f/b A or D, f/b 1, 3, 5 or 6, f/b 1, 2 or 3, f/b L or blank												
	R	0.1	125	50-60	130	1/2 or 1/1-2.3 or 1.2	6K	50K	--	micro	2A, 2B, 2C, 2D	-
	R	0.1	250	50-60	130	1/2 or 1/1-2.3 or 1.2	6K	50K	--			
	R	0.1	30	DC	130	1/2 or 1/1-2.3 or 1.2	6K	50K	--			
SZM-V02 f/b number or blank, f/b F, f/b D, f/b 5 or 6, f/b -3												
	R	0.2	30	DC	130	1/1-1.2	6K	100K	--	micro	09N01, 14N03	-
	R	0.1	40	DC	130	1/1-1.2	6K	100K	--			
SZM-V1 f/b numbers or blank, f/b F, f/b A, C or D, f/b 1, 3, 5, 6, 8 or 9, f/b 1, 2 or 3												
	R	1	125	50-60	130	1/2-2.2	6K	10K	--	micro	1A, 1B	-
	R	1	250	50-60	130	1/2-2.2	6K	10K	--			
	R	0.1	30	DC	130	1/2-2.2	6K	10K	--			
SZM-V11 f/b numbers or blank, f/b F, f/b A, C or D, f/b 3, 5, 6, 8 or 9, f/b 1, 2 or 3, f/b L or blank												
	R	11	125	50-60	130	1/2 or 1/1-2.3 or 1.2	6K	50K	--	micro	3A, 3B, 3C, 3D	-
	R	11	250	50-60	130	1/2 or 1/1-2.3 or 1.2	6K	50K	--			
	R	0.6	125	DC	130	1/2 or 1/1-2.3 or 1.2	6K	50K	--			
	R	0.3	250	DC	130	1/2 or 1/1-2.3 or 1.2	6K	50K	--			
SZM-V16 f/b number or blank, f/b F, f/b A, C, or D, f/b 6, 8, 9, or G, f/b -1, -2, or -3, f/b L or blank												
	R	16	125	50-60	130	1/2 or 1/1-2.2 or 1.2	6K	50K	--	micro	14N03	-
	R	16	250	50-60	130	1/2 or 1/1-2.2 or 1.2	6K	50K	--			
	R	0.6	125	DC	130		6K	50K	--			

						1/2 or 1/1-2.2 or 1.2						
	R	0.6	250	DC	130	1/2 or 1/1-2.2 or 1.2	6K	50K	--			
	hp	1/2	250	50-60	130	1/2 or 1/1-2.2 or 1.2	6K	6K	--			
SZM-V6 f/b number or blank, f/b F, f/b A, C or D, f/b 1, 3, 5, 6, 8 or 9, f/b 1, 2, or 3, f/b L or blank												
	R	6	125	50-60	130	1/2 or 1/1-2.2 or 1.2	6K	50K	--	micro	4A, 4B, 4C, 4D	-
	R	6	250	50-60	130	1/2 or 1/1-2.2 or 1.2	6K	50K	--			
	R	0.4	125	DC	130	1/2 or 1/1-2.2 or 1.2	6K	50K	--			
	R	0.2	250	DC	130	1/2 or 1/1-2.2 or 1.2	6K	50K	--			
	R	0.3	30	DC	130	1/2 or 1/1-2.2 or 1.2	6K	50K	--			

\* - With suffixes.

Note 1A - IP40 testing was completed on the complete switch without an end product enclosure. The switch gasket (seal) to the end product enclosure is evaluated in the end product testing.

Note 1B - The terminals of the switch employ 4.8 x 0.5 mm or 6.3 x 0.8 mm quick-connect tabs, the terminals have been investigated for use with prepared conductor of specified size 0.5 mm2 stranded wire only.

Note 2A - The Switch body is installed inside of end product; consider for non-accessible parts. When mounted in accordance with the manufactures instruction, this switch gets a protection degree of IP 40.

Note 2B - IP40 testing was completed on the complete switch without an end product enclosure. The switch gasket (seal) to the end product enclosure is evaluated in the end product testing.

Note 2C - The terminals of the switch employ 4.8 x 0.5 mm quick-connect tabs, the terminals have been investigated for use with prepared conductor of specified size 0.5 mm2 stranded wire only.

Note 2D - All the plastic parts of Models SZM-V01 f/b suffix is identical to Models SZM-V1 f/b suffix in all respects including constructions and materials. Based on the test results of SZM-V1, GLOW WIRE IGNITION TEMPERATURE TEST was waived. Refer to E177511, Report dated 2012-09-14, Test Record No. 1.

Note 3A - The Switch body is installed inside of end product; consider for non-accessible parts. When mounted in accordance with the manufactures instruction, this switch gets a protection degree of IP 40.

Note 3B - IP40 testing was completed on the complete switch without an end product enclosure. The switch gasket (seal) to the end product enclosure is evaluated in the end product testing.

Note 3C - The terminals of the switch employ 4.8 x 0.5 mm or 4.8 x 0.8 mm or 6.3 x 0.8 mm quick-connect tabs, the terminals have been investigated for use with prepared conductor of specified size 1.5 mm2 stranded wire only.

Note 3D - All the plastic parts of Models SZM-V11 f/b suffix is identical to Models SZM-V1 f/b suffix in all respects including constructions and materials. Based on the test results of SZM-V1, GLOW WIRE IGNITION TEMPERATURE TEST were waived. Refer to E177511, Report dated 2012-09-14, Test Record No. 1.

Marking: Company name or trademark  ,  , catalog, model or part number, electrical ratings and the  Recognized Component Mark for Canada, on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2017-05-30

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

◆ 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".